

THERMOSIPHON SYSTEM FINO 300-2-T200

Technical Specifications

300-2-T200

Collector

Number of collectors	2
Area of collector	3.82m ²
Absorber Surface	3.42m ²
Weight	41kg each

Absorber Fins	Aluminum full face sheet with blue selective titanium oxides sputtering treatment. Welded to copper pipe with laser welding. a = 95% e = 5% (±0.02)
---------------	--------------------------------------------------------------------------------------------------------------------------------------------------------

Casing	Aluminum profile epoxy powder oven painted. Free of screws and rivets. Sea Water resistant.
--------	---------------------------------------------------------------------------------------------

Glassing	Tempered low iron glass 4 mm. 88.5% transmission.
----------	---------------------------------------------------

Sealing	EPDM Rubber
---------	-------------

Tank

Nominal Capacity	300ltr
------------------	--------

Dimensions	2080mm x Ø530
------------	---------------

Weight empty	106kg
--------------	-------

Weight filled	396.50kg
---------------	----------

Boiler body	The boiler "body" is made from 2.5mm USD 37.2 steel plate. The boiler is (glass) enameled with the advanced double "direct" method "fired" at 860°C
-------------	-----------------------------------------------------------------------------------------------------------------------------------------------------

Heat exchanger	Internal "double jacket" heat exchanger made from 1.5 mm U.S.D. 37.2 steel sheet
----------------	----------------------------------------------------------------------------------

Insulation	Polyurethane 40mm thickness casted under pressure with density 40kg/m ³
------------	------------------------------------------------------------------------------------

External Cover	Silver color (Stainless steel cover is optional)
----------------	--------------------------------------------------

Anode protection	Magnesium rod
------------------	---------------

Solar Safety Valve	Safety valve: 2.5at
--------------------	---------------------

Max. working pressure	10 at
-----------------------	-------

Electric element 2-4kW

